



Size Board

LENGTH	610 mm
WIDTH	122 mm
TOTAL THICKNESS	15 mm
THICKNESS TOP LAYER	4 mm

Size Pack

PACK LENGTH	1230 mm
PACK WIDTH	130 mm
PACK THICKNESS	125 mm
PACK WEIGHT	13 kg
LAYERS/PACK	16
M²/PACK	1.19 m ²

Size Pallet

LENGTH PALLET	1250 mm
WIDTH PALLET	1040 mm
HEIGHT PALLET	870 mm
WEIGHT PALLET	1263 kg
PACKS/PALLET	96
M²/PALLET	114.24 m ²

Characteristics

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Mongolica
GRADE	ABC
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	4 mm
STRIPS	90° - 8x left + 8x right
CUTTING METHOD	Sawn veneer
BEVEL	No bevel
COLOUR FINISH	Unfinished
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Multiplex support
WOOD SPECIES SUPPORT	Mixed Light Hardwood
SUPPORT CONSTRUCTION	Multiplex (8 layers)
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Crosswise (Casco)

Installation

SYSTEM

Tongue and groove system



APPLICATIONS

- Light household use
- Moderate commercial use
- Normal commercial use
- Normal household use
- Intensive commercial use

UNDERFLOOR HEATING

Yes

RESANDABLE

Resandable

Certification

This product conforms to CE standard EN 14342:2005 + A1: 2008 - Level 4 for flooring type BS EN 13489:2002 (Wood and parquet flooring, Multilayer parquet)

- Formaldehyde emission, determined according to standard EN 13183-1: E1
- Moisture content, determined according to standard EN 13183-1: 10% (+ / -2%). Fits in dry areas with a moisture content of 50% to 60%
- Width Shrinkage, complies with standard EN 13647
- Reaction to fire, determined according to standard EN 13501-1: Dfl-S1
- Does not contain any PCP (pentachlorophenol)

Technical specifications

- Hardness: N / mm² (Birrell Hardness) 3.40
- Thermal conductivity: λ 14, 00 (W / (mk)) R = 0.11 m² K / W

Additional tests:

- Tested for delamination and stability according to standard EN1910 (cf. 15-189-BRUT CLASSIC)
- The bonding was tested according to EN311 standard (see 15-189-BRUT CLASSIC)