



Size Board

LENGTH	540 mm
WIDTH	90 mm
TOTAL THICKNESS	15 mm
THICKNESS TOP LAYER	4 mm

Size Pack

PACK LENGTH	600 mm
PACK WIDTH	190 mm
PACK THICKNESS	125 mm
PACK WEIGHT	8 kg
LAYERS/PACK	16
M²/PACK	0.78 m ²

Size Pallet

LENGTH PALLET	1810 mm
WIDTH PALLET	1000 mm
HEIGHT PALLET	870 mm
WEIGHT PALLET	655 kg
PACKS/PALLET	80
M²/PALLET	61.4 m ²

Characteristics


Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABC
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	4 mm
STRIPS	1 strip
CUTTING METHOD	Sawn veneer
BEVEL	Micro bevel Four sides (0,50 mm)
COLOUR FINISH	Smoked Unfinished
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Multiplex support
WOOD SPECIES SUPPORT	Mixed Light Hardwood
SUPPORT CONSTRUCTION	Multiplex (8 layers)
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Crosswise (Casco)

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove system	Light household use	Yes
	Moderate commercial use	RESANDABLE
	Take the necessary precautions for use in wet areas	Resandable
	Normal commercial use	
	Normal household use	
	Intensive commercial use	

Certification

This product conforms to CE standard EN 14342:2005 + A1: 2008 - Level 4 for flooring type BS EN 13489:2002 (Wood and parquet flooring, Multilayer parquet)

- Formaldehyde emission, determined according to standard EN 13183-1: E1
- Moisture content, determined according to standard EN 13183-1: 10% (+ / -2%). Fits in dry areas with a moisture content of 50% to 60%
- Width Shrinkage, complies with standard EN 13647
- Reaction to fire, determined according to standard EN 13501-1: Dfl-S1
- Does not contain any PCP (pentachlorophenol)

Technical specifications

- Hardness: N / mm² (Birrell Hardness) 3.40
- Thermal conductivity: λ 14, 00 (W / (mk)) R = 0.11 m² K / W

Additional tests:

- Tested for delamination and stability according to standard EN1910 (cf. 15-189-BRUT CLASSIC)
- The bonding was tested according to EN311 standard (see 15-189-BRUT CLASSIC)